

## Comfort garment that helps to reduce heat stress

- Reduces heat stress by absorbing heat from the body
- Can be worn underneath chemical protective clothing, turnout gear, coveralls, diving suits or daily workwear
- Integrated cooling elements for comfort and retained wearer flexibility
- Cooling elements recharge at room temperature
- Easy to dress
- Washable
- Long life time
- Available in a flame retardant version



ActivArmR™ Cooling Vest with PCM (phase change material) elements.



ActivArmR™ Standard Cooling Vest, 97-609



ActivArmR™ FR Cooling Vest, 97-610

### Applications

- Chemical industry
- Diving
- Fire & Rescue services
- Military
- Mining
- Oil platforms
- Nuclear plants
- Paper mills
- Police
- Refineries
- Steel industry

### PRODUCT INFORMATION

	ActivArm <sup>™</sup> Cooling Vest
<b>Product description</b>	Cooling vest with front hook & loop closure and integrated cooling elements. The vest reduces heat stress by absorbing heat from the body and thus prevents elevated body temperatures in people who work in hot environments or with extreme physical exertion. Can be worn underneath chemical protective clothing, turnout gear, coveralls, diving suits or daily workwear.
<b>Available models</b>	Standard and FR (flame retardant).
<b>Material &amp; Colour</b>	<b>Standard model 97-609:</b> Knitted polyester, black <b>FR model 97-610:</b> Marko® flame retardant material (54% modacrylic, 44% cotton, 2% antistatic fibers), dark blue
<b>Cooling elements</b>	20 pcs aluminum bags with PCM (phase change material). Non-toxic, non-flammable. The cooling elements are integrated into the vest lining for comfort and retained wearer flexibility.
<b>Phase change temperature</b>	28 °C / 82 °F
<b>Cooling effect, duration</b>	@ 60 °C / 140 °F: approx. 90 minutes @ 45 °C / 113 °F: approx. 4 hours
<b>Regeneration time</b>	@ 22 °C / 72 °F: 2-3 hours @ 8 °C / 46 °F: 30 minutes <b>Freezer / ice water:</b> 5-10 minutes
<b>Weight</b>	Approx. 2.1 kg (4.6 lbs) incl. cooling elements.
<b>Sizes</b>	S/M, L/XL, 2XL/3XL, 4XL/5XL
<b>Laundering</b>	Yes, in water @40 °C. Do not tumble dry. PCM elements to be removed before washing.
<b>Reusability</b>	The PCM elements will last at least 1000 cycles of recharging, if properly maintained.
<b>Approvals</b>	<ul style="list-style-type: none"> <li>The FR material is tested according to EN ISO 11612.</li> <li>The complete Cooling Vest is not tested nor approved as fire or heat protective garment.</li> </ul>

### For additional information, visit us at [protective.ansell.com](http://protective.ansell.com) or contact us at:

**Ansell Protective Solutions AB**  
Arenagatan 8B  
215 33 Malmö  
Sweden  
Tel. + 46 10 205 1800  
[order.protective@ansell.com](mailto:order.protective@ansell.com)

**Europe, Middle East and Africa**  
Ansell Healthcare Europe NV  
Riverside Business Park  
Blvd International, 55  
1070 Brussels, Belgium  
Tel. + 32 2 528 74 00  
Fax + 32 2 528 74 01  
[info.europe@ansell.com](mailto:info.europe@ansell.com)

**Latin America & Caribbean**  
Ansell Brazil Ltda.  
Rua das Figueiras 474 – 4º Andar  
Bairro Jardim  
SP 09080-300 Santo André, Brazil  
CNPJ: 03.496.778/0001-21  
+55 11 3356 3100  
[sac@ansell.com](mailto:sac@ansell.com)

**North America**  
Ansell Healthcare LLC  
111 Wood Avenue South, Suite 210  
Iselin, NJ 08830, USA  
Tel. + 1 800 800 0444  
Fax. + 1 800 800 0445  
[info@ansell.com](mailto:info@ansell.com)

**Asia Pacific**  
Ansell Protective Solutions Singapore Pte. Ltd.  
237, Pandan Loop,  
#05-05 Westech Building  
128424 Singapore  
Tel. + 65 6908 4115  
[order.protective@ansell.com](mailto:order.protective@ansell.com)