



471-TH



**TOOLS@HEIGHT ADJUSTABLE HOOK SPANNER WRENCHES**

Industrial Black Finish, SAE

| Product Code | Span Diameter (Inches) | Hook Depth (Inches) | Hook Thickness (Inches) | Overall Length (Inches) | Weight (lbs.) |
|--------------|------------------------|---------------------|-------------------------|-------------------------|---------------|
| 471-TH       | 3/4 to 2               | 1/8                 | 1 1/32                  | 5 3/8                   | .26           |
| 472-TH       | 1 1/4 to 3             | 5/32                | 1 3/32                  | 7 1/4                   | .49           |
| 474-TH       | 2 to 4 3/4             | 3/16                | 1 5/32                  | 11 1/2                  | .97           |
| 474A-TH      | 4 1/2 to 6 1/4         | 1/4                 | 1 5/32                  | 17 1/2                  | 1.05          |

**Features**

- Ideal for adjusting collars, lock nut rings, and bearings.
- Specifically engineered to hold up under the most rigorous industrial use.



483-TH



484-TH



**TOOLS@HEIGHT ADJUSTABLE FACE SPANNER WRENCHES**

Industrial Black Finish, SAE

| Product Code | Span Diameter (Inches) | Pin Diameter (Inches) | Pin Length (Inches) | Overall Length (Inches) | Weight (lbs.) |
|--------------|------------------------|-----------------------|---------------------|-------------------------|---------------|
| 482-TH       | 2                      | 3/16                  | 1/4                 | 6 1/4                   | .31           |
| 483-TH       | 3                      | 1/4                   | 1/4                 | 8 1/8                   | .63           |
| 484-TH       | 4                      | 5/16                  | 1/2                 | 10 3/8                  | 1.01          |

**Features**

- Ideal for adjusting collars, lock nut rings, and bearings.
- Specifically engineered to hold up under the most rigorous industrial use.



**TOOLS@HEIGHT T-HANDLE HEX DRIVERS**

SAE & Metric

| Product Code | Shaft Length (Inches) | Size (Inches) | Weight (lbs.) |
|--------------|-----------------------|---------------|---------------|
| 900T-094-TH  | 4 1/8                 | 3/32          | 0.09          |
| 900T-109-TH  | 4 1/8                 | 7/64          | 0.08          |
| 900T-125-TH  | 4 1/8                 | 1/8           | 0.12          |
| 900T-141-TH  | 4 1/8                 | 9/64          | 0.09          |
| 900T-156-TH  | 5 1/2                 | 5/32          | 0.11          |
| 900T-188-TH  | 5 1/2                 | 3/16          | 0.19          |
| 900T-219-TH  | 5 1/2                 | 7/32          | 0.23          |
| 900T-250-TH  | 7 1/4                 | 1/4           | 0.28          |
| 900T-313-TH  | 7 1/4                 | 5/16          | 0.39          |
| 900T-375-TH  | 7 1/4                 | 3/8           | 0.51          |

**Features**

- Comfort grip handle for durability and flexibility in all types of work applications
- Black oxide tips prevent chipping of chrome to reduce possible contamination at work location
- For use with optional WTHUNIRET1 Retractable Lanyard



900T-250-TH

Any tool that weighs more than 5 pounds should be attached to an anchor point such as a work platform or utility bucket rather than the operator.