



## B142PZ

### BahcoFit VDE Insulated Pozidriv Screwdrivers with Multi-Component Handle PZ0-PZ3



#### PRODUCT DETAILS







- Insulated VDE Screwdriver for Pozidriv head screws
- Phosphate finish tip for higher accuracy
- 2-Component handle with a large zone of soft grip for comfortable grip and high torque transfer
- Permanent symbol and markings on the handle for quick identification of the tip
- Integrated hanging hole
- For work on live equipment, up to 1000 V, high quality blade insulation that is moulded directly onto the blade
- Individually inspected and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 8764/DIN 5260
- SB = Retailed packed on a plastic hanger
- Comfortable to use with two-component handle of over 75% rubber
- Maximum grip thanks to the vertical anti-slip grooves in the handle
- Easy size and screw type identification from the markings on the handle
- High-performance insulated alloy steel shaft with phosphate finish tip



Follow the Fish!



## PRODUCT ATTRIBUTES

Product						
<b>B142.000.075</b>	PZ0	75 mm	24,5 mm	95 mm	170 mm	30 g
<b>B142.001.080</b>	PZ1	80 mm	24,5 mm	95 mm	175 mm	40 g
<b>B142.001.150</b>	PZ1	150 mm	30 mm	105 mm	255 mm	90 g
<b>B142.002.100</b>	PZ2	100 mm	30 mm	105 mm	205 mm	80 g
<b>B142.002.175</b>	PZ2	175 mm	34 mm	117 mm	292 mm	140 g
<b>B142.003.150</b>	PZ3	150 mm	34 mm	117 mm	267 mm	150 g
<b>SB142.000.075</b>	PZ0	75 mm	24,5 mm	95 mm	170 mm	34 g
<b>SB142.001.080</b>	PZ1	80 mm	24,5 mm	95 mm	175 mm	44 g
<b>SB142.002.100</b>	PZ2	100 mm	30 mm	105 mm	205 mm	84 g
<b>SB142.003.150</b>	PZ3	150 mm	34 mm	117 mm	267 mm	154 g

