


Quick Weld Ferrules

Features:

- 304 stainless construction
- just slip onto sanitary OD tube and weld
- butt weld is not needed

Tube OD	Dimensions			304 Stainless Steel	
	A	B	C	Part #	Price/E
1"	0.290"	1.005"	0.870"	14QMP-G100	\$7.45
1½"	0.199"	1.505"	1.370"	14QMP-G150	7.45
2"	0.205"	2.005"	1.870"	14QMP-G200	9.50
2½"	0.210"	2.505"	2.370"	14QMP-G250	11.45
3"	0.257"	3.005"	2.870"	14QMP-G300	14.35
4"	0.235"	4.005"	3.834"	14QMP-G400	21.80
6"	0.321"	6.005"	5.782"	14QMP-G600	56.15



Breakaway Coupling - Clamp

Applications:

- Minimizes spillage and damage associated with pull away and drive away incidents

Features:

- designed to be installed between a fixed point and a hose
- coupling breaks away with an excessive load
- EPDM standard clamp gasket
- working pressure: 350 PSI @ 70°F
- 13kN break load bolts standard, other break loads available
- 316 stainless steel polished to standard <math><32R_a</math>, 3A finish
- other sizes, gaskets and connections available, contact Dixon™



Size	316 Stainless Steel	
	Part #	Price/E
3"	SBC-E300CC13	\$613.80

Breakaway Coupling Dimensions

