

DRIFIRE HYDROflash FR Foul Weather Hood - Navy



Specs

Product Code	HYDROFLASHH-N
Sizes	One Size Fits Most
Stock Colors	
Fabric / Material	GORE-TEX PYRAD® Polyester on ePTFE

Compliance

Arc Rating 15 cal/cm²

CAT Level CAT 2

Standards

- ASTM F2733
- ASTM F1891
- CSA Z462
- ASTM F903
- OSHA 1910.269
- Gas Probe Shirley Method 138:2000, EN 1149-3/2004 & EN 1149-5/2008

Features

Features

- HYDROFlash FR™ (2 Layer PYRAD) is the lightest weight waterproof, breathable Flash Fire rated garment available
- Lightweight, breathable, and fast drying
- 100% waterproof and windproof
- Resists cold cracking in low temperatures
- Hot liquid and steam resistant
- Petroleum and oil-based mud resistant
- Detachable, snap-on jacket hood is sold separately
- Hook and loop adjustment for secure fit
- Field repair kit is available (sold separately)
- Made in the USA

Product Care

Product Care

- READ THE GARMENT LABEL AND LAUNDRER PER INSTRUCTIONS ON GARMENT LABEL.
- DO NOT use bleach or hydrogen peroxide. DO NOT use fabric softeners.
- Wash/Laundering Instructions: Wash separately from other garments. Machine wash warm (max. 120°F/50°C) using mild detergent. Rinse 4 times (adding extra rinse to standard 3-rinse cycle) to remove all soil and detergent residues. Dawn Dish Liquid is recommended for oil based stains. Pre-treat the area, soak for stubborn stains or mild stain treatments may be used. Ensure the product is completely rinsed from the fabric before drying.
- Drying: Turn garment inside out before drying. Tumble dry using permanent press setting (medium). Tumble drying is recommended to protect garment's water repellent treatment.
- Wash according to the instructions above to remove any contaminants in order to maintain fabric performance when garment becomes soiled with dirt, greases, oils, etc.
- If contaminants cannot be removed after laundering, it is best to discontinue use of garment.

