



# PRODUCT DATA SHEET



Silaramic® Brake System Grease, 9 Wt Oz  
 No. 05363 | Item# 1003796 | Case# 1003795

Product Description	A synthetic, dry-film, ceramic lubricant formulated to reduce brake noise and vibrations by dampening all brake vibrating frequencies. Will not run off or wash out. Works in extreme temp ranges from -50 to 3000°F. Protects against uneven pad wear.
Applications	All brake systems and brake components, including calipers, bushings, holes, pins, inserts, anchors, bolts, calipers and boots
Unit Package Description	9 Ounce Tub with Brush
Brand	CRC
Generic Description 1	Brake System Grease
Net Fill	9 Wt Oz
UPC Code	078254053639
Unit Dimensions	4.25H x 3.88W x 3.88D in
Units Per Case	12
Case Dimensions	5H x 12.25W x 16D in
Cases Per Pallet	175
Case Weight	8 lbs
I 2 of 5 Code	30078254053630
Appearance	Off White Semi Solid Grease
Base Type	Polydimethylsiloxane
Flash point (F)	550°F
Flash point (C)	288°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	1.0
NLGI Grade	2
Timken OK Load Lbs.	Not Determined
Plastic Safe	Yes
Evaporation Rate	Very Slow
Dielectric Strength	Not Determined

Last revised: 11/30/2017  
 Page 1 of 2



Customer Care: 800-556-5074  
 Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	-50 to 3000°F
Working Temp (C)	-45.6 to 1648.89°C
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	None
Elastomer Compatibility	Compatible
Leakage	0.2
Low Temp Torque	Not Determined
Oil Separation	0.2
Oxidation Stability	Not Determined
Pour Point (F)	Not Determined
Water Washout	0.25
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with petroleum solvents.

Last revised: 11/30/2017  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.