

MSA Duo-Flo™ Respirators



Designed for Torus and Wetwell Abrasive Blasting

MSA's custom designed products for Torus and Wetwell blasting include the Duo-Flo Respirator with a tight-fitting facepiece, a durable hood that provides head, neck and upper body protection and replacement 3-layer lens covers for workers engaged in abrasive blasting.

The Constant Flow Duo-Flo Option is designed to handle both air-supplied and air-purifying (P100) modes of operation.

The 3-layer cover lens allows for lens removal without stopping work.

The shoulder length hood is made of cotton-polyester material. It has an elastic neck and Velcro closures for comfortable sealing around the neck.

- APR filter for Entry/Egress.
- Constant flow Airline with Type CE approval for blasting operations.
- Customized blasting hood designed specifically for maximum vision and mobility.
- Standard Ultravue® Facepiece maximizes vision in tight quarters.
- Easy integration with Fall Protection.
- NIOSH Approved



PN 466095



PN 10125492



PN 10125177

Ordering Information

DUO-FLO RESPIRATORS	466095	Constant Flow Duo-Flo Respirator w/full-face Ultravue Facepiece, Foster fittings, one P100 Ultra Filter
REPLACEMENT CARTRIDGES <i>for Duo-Flo Respirators</i>	10010420	Round Ultra Filter Cartridge, box of 6
	10010421	Round Ultra Filter Cartridge, box of 50
HOODS	10125492	Torus Blast Hoods, box of 20*
LENS COVERS	10125177	Replacement lens covers 3/stack, package of 5

* Required for Abrasive Blasting Approval

	Small	Medium	Large	
ULTRAVUE FACEPIECE	480251	480247	480255	Black Silicone
	471218	457126	471230	Black Hycar

	Material	Hose Coupling	50ft	25ft	15ft	8ft
AIR-SUPPLY HOSE	Neoprene	Brass	455022	455021	455020	481071

QUICK-DISCONNECT TYPE	Interchangeability	1	2	3	4	5*
		Female Socket 1/4" NPT	Male Plug w/Female 1/4" NPT	Union Adapter 1/4" NPT x 3/4" UNF	Male Plug w/Male 1/4" NPT (used when connecting Inlet Pressure Gauge)	Female Socket Assy. (used to connect Air-Supply Hose to Male Plug on Respirator)
FOSTER (S)	B	628770	55716	69542	56549	467044

Call customer service 1-800-MSA-2222 for other available options or fittings.