



<b>Product Codes</b>	SPXHPCA0208__RG SPXHPCA0208__LN
<b>Material</b>	6.4 oz. OPF Blend, Twill
<b>Features</b>	<ul style="list-style-type: none"> <li>•FR Fabric will NOT melt, drip, or ignite</li> <li>•Covered FR zip front closure with additional snaps</li> <li>•Inset elastic waistband</li> <li>•Action back for increased movement</li> <li>•Two chest pockets with flaps and snap closure</li> <li>•Exceptional tensile and tear strength</li> <li>•Moisture wicking</li> <li>•Excellent comfort and durable protection</li> </ul>
<b>Standards</b>	<p>Meets OSHA 1910.269                      Compliant to NFPA 70E for Arc Flash                      CSA Z462 Compliant for Arc Flash (Canada)                      Meets ASTM F1506-10a                      Passes EN ISO 11611 A1, Class 2; A2, Class 2; 6.8 impact of spatter, Class 2;                      6.9 Heat transfer (Radiation), Class 1                      Anti-Static per EN 1149-5 (Meets requirements for shielding factor and half decay time)</p>
<b>Arc Rating</b>	9.4 cal/cm <sup>2</sup> ; CAT 2
<b>Sizes</b>	SM-4X- Made to Order Regular, Long- Made to Order
<b>Applications</b>	Welding Molten Metals Steel Industry General FR Applications Utilities Construction



**NATIONAL SAFETY APPAREL®**