

DP1200 Series Disposable Uncorded Earplugs

NRR 30dB

Soft foam earplugs gently expand and self adjust to all size ear canals

PART NO.

DP1200 •

STANDARDS

Meets ANSI S3.19-1974

GENERAL SPECIFICATIONS

Noise Reduction Rating (NRR) : 30dB

Restrictions of Hazardous Substances (RoHS) complaint

Hearing protection style: Uncorded plug

Reusable: No

Metal detachable: No

Shape: Bell

MATERIALS

Plug : Polyurethane foam

COLOR

Plug color: green

SIZE

Plug length: 2.5mm

Plug diameter: 1.5mm



PRODUCT GUIDELINES

The level of noise entering a person's ear, when hearing protection is worn as directed is closely approximated by the difference between the A-weighted environmental level and the NRR.

Example: 1. The environmental noise level at the ear is 92 dB(A).

2. The NRR is 30 decibels (dB).

3. The level of noise entering the ear is approximately equal to 60 dB(A).

CAUTION: For noise environments dominated by frequencies below 500 Hz, the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Plugs should be inserted with a gentle rocking; twisting motion while opposite hand is opening ear canal by pulling the top of ear. Although hearing protectors can be recommended for protection against the harmful effects of impulse noise, the Noise Reduction Rating (NRR) is based on the attenuation noise and may not be an accurate indicator of the protection attainable against impulsive noise, such as gunfire.