

Series 142P Fractional	Hardness	Vc (sfm)	DC • in								
			1/8	3/16	1/4	3/8	1/2	5/8	3/4		
P	CARBON STEELS 1018, 1040, 1080, 1090, 10L50, 1140, 1212, 12L15, 1525, 1536	≤ 175 Bhn or ≤ 7 HRc (340-510)	425	RPM	12988	8659	6494	4329	3247	2598	2165
				Fr	0.0043	0.0065	0.0086	0.0129	0.0172	0.0216	0.0259
				Feed (ipm)	56.0	56.0	56.0	56.0	56.0	56.0	56.0
		≤ 275 Bhn or ≤ 28 HRc (304-456)	380	RPM	11613	7742	5806	3871	2903	2323	1935
				Fr	0.0039	0.0058	0.0078	0.0116	0.0155	0.0194	0.0233
				Feed (ipm)	45.0	45.0	45.0	45.0	45.0	45.0	45.0
		≤ 425 Bhn or ≤ 45 HRc (176-264)	220	RPM	6723	4482	3362	2241	1681	1345	1121
				Fr	0.0033	0.0049	0.0065	0.0098	0.0131	0.0164	0.0196
				Feed (ipm)	22.0	22.0	22.0	22.0	22.0	22.0	22.0
	ALLOY STEELS 4140, 4150, 4320, 5120, 5150, 8630, 86L20, 50100	≤ 275 Bhn or ≤ 28 HRc (264-396)	330	RPM	10085	6723	5042	3362	2521	2017	1681
				Fr	0.0033	0.0049	0.0065	0.0098	0.0131	0.0164	0.0196
				Feed (ipm)	33.0	33.0	33.0	33.0	33.0	33.0	33.0
		≤ 375 Bhn or ≤ 40 HRc (160-240)	200	RPM	6112	4075	3056	2037	1528	1222	1019
				Fr	0.0028	0.0042	0.0056	0.0083	0.0111	0.0139	0.0167
				Feed (ipm)	17.0	17.0	17.0	17.0	17.0	17.0	17.0
		≤ 425 Bhn or ≤ 45 HRc (112-168)	140	RPM	4278	2852	2139	1426	1070	856	713
				Fr	0.0020	0.0030	0.0040	0.0060	0.0079	0.0099	0.0119
				Feed (ipm)	8.5	8.5	8.5	8.5	8.5	8.5	8.5
	TOOL STEELS A2, D2, H13, L2, M2, P20, S7, T15, W2	≤ 200 Bhn or ≤ 13 HRc (116-174)	145	RPM	4431	2954	2216	1477	1108	886	739
				Fr	0.0028	0.0042	0.0056	0.0085	0.0113	0.0141	0.0169
				Feed (ipm)	12.5	12.5	12.5	12.5	12.5	12.5	12.5
		≤ 375 Bhn or ≤ 40 HRc (76-114)	95	RPM	2903	1935	1452	968	726	581	484
				Fr	0.0013	0.0020	0.0027	0.0040	0.0054	0.0067	0.0081
				Feed (ipm)	3.9	3.9	3.9	3.9	3.9	3.9	3.9
M	STAINLESS STEELS (FREE MACHINING) 303, 416, 420F, 430F, 440F	≤ 185 Bhn or ≤ 9 HRc (244-366)	305	RPM	9321	6214	4660	3107	2330	1864	1553
				Fr	0.0026	0.0039	0.0051	0.0077	0.0103	0.0129	0.0154
				Feed (ipm)	24.0	24.0	24.0	24.0	24.0	24.0	24.0
		≤ 275 Bhn or ≤ 28 HRc (156-234)	195	RPM	5959	3973	2980	1986	1490	1192	993
				Fr	0.0020	0.0030	0.0040	0.0060	0.0081	0.0101	0.0121
				Feed (ipm)	12.0	12.0	12.0	12.0	12.0	12.0	12.0
	STAINLESS STEELS (DIFFICULT) 304, 316, 321, 13-8 PH, 15-5PH, 17-4 PH, Custom 450	≤ 275 Bhn or ≤ 28 HRc (120-180)	150	RPM	4584	3056	2292	1528	1146	917	764
				Fr	0.0020	0.0030	0.0040	0.0060	0.0079	0.0099	0.0119
				Feed (ipm)	9.1	9.1	9.1	9.1	9.1	9.1	9.1
		≤ 375 Bhn or ≤ 40 HRc (88-132)	110	RPM	3362	2241	1681	1121	840	672	560
				Fr	0.0018	0.0027	0.0036	0.0054	0.0071	0.0089	0.0107
				Feed (ipm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0
K	CAST IRONS Gray, Malleable, Ductile	≤ 220 Bhn or ≤ 19 HRc (288-432)	360	RPM	11002	7334	5501	3667	2750	2200	1834
				Fr	0.0045	0.0068	0.0091	0.0136	0.0182	0.0227	0.0273
				Feed (ipm)	50.0	50.0	50.0	50.0	50.0	50.0	50.0
		≤ 260 Bhn or ≤ 26 HRc (268-402)	335	RPM	10238	6825	5119	3413	2559	2048	1706
				Fr	0.0045	0.0068	0.0091	0.0136	0.0182	0.0227	0.0273
				Feed (ipm)	46.5	46.5	46.5	46.5	46.5	46.5	46.5

continued on next page

Series 142P Fractional		Hardness	Vc (sfm)	DC • in							
				1/8	3/16	1/4	3/8	1/2	5/8	3/4	
N	ALUMINUM ALLOYS 2017, 2024, 356, 6061, 7075	≤ 80 Bhn or ≤ 47 HRb	770	RPM	23531	15687	11766	7844	5883	4706	3922
			(616-924)	Fr	0.0049	0.0073	0.0098	0.0147	0.0195	0.0244	0.0293
				Feed (ipm)	115.0	115.0	115.0	115.0	115.0	115.0	115.0
		≤ 150 Bhn or ≤ 8 HRb	660	RPM	20170	13446	10085	6723	5042	4034	3362
			(528-792)	Fr	0.0050	0.0074	0.0099	0.0149	0.0198	0.0248	0.0297
				Feed (ipm)	100.0	100.0	100.0	100.0	100.0	100.0	100.0
	COPPER ALLOYS Alum Bronze, C110, Muntz Brass	≤ 140 Bhn or ≤ 3 HRc	550	RPM	16808	11205	8404	5603	4202	3362	2801
			(440-660)	Fr	0.0020	0.0030	0.0040	0.0060	0.0080	0.0100	0.0120
				Feed (ipm)	33.5	33.5	33.5	33.5	33.5	33.5	33.5
		≤ 200 Bhn or ≤ 23 HRc	440	RPM	13446	8964	6723	4482	3362	2689	2241
			(352-528)	Fr	0.0020	0.0030	0.0040	0.0060	0.0080	0.0100	0.0120
				Feed (ipm)	27.0	27.0	27.0	27.0	27.0	27.0	27.0
S	HIGH TEMP ALLOYS (NICKEL , COBALT, IRON BASE) Inconel 601, 617, 625, Incoloy, Monel 400, Rene, Waspaloy	≤ 300 Bhn or ≤ 32 HRc	95	RPM	2903	1935	1452	968	726	581	484
			(76-114)	Fr	0.0008	0.0012	0.0016	0.0024	0.0032	0.0040	0.0048
				Feed (ipm)	2.3	2.3	2.3	2.3	2.3	2.3	2.3
		≤ 400 Bhn or ≤ 43 HRc	50	RPM	1528	1019	764	509	382	306	255
			(40-60)	Fr	0.0007	0.0010	0.0013	0.0020	0.0026	0.0033	0.0039
				Feed (ipm)	1.0	1.0	1.0	1.0	1.0	1.0	1.0
	TITANIUM ALLOYS Pure Titanium, Ti6Al4V, Ti6Al2Sn4Zr2Mo, Ti4Al4Mo2Sn0.5Si, Ti-6Al4V	≤ 275 Bhn or ≤ 28 HRc	215	RPM	6570	4380	3285	2190	1643	1314	1095
			(172-258)	Fr	0.0018	0.0026	0.0035	0.0053	0.0070	0.0088	0.0105
				Feed (ipm)	11.5	11.5	11.5	11.5	11.5	11.5	11.5
		≤ 350 Bhn or ≤ 38 HRc	160	RPM	4890	3260	2445	1630	1222	978	815
			(128-192)	Fr	0.0016	0.0024	0.0032	0.0048	0.0064	0.0080	0.0096
				Feed (ipm)	7.8	7.8	7.8	7.8	7.8	7.8	7.8
H	TOOL STEELS A2, D2, H13, L2, M2, P20, S7, T15, W2	≤ 475 Bhn or ≤ 50 HRc	85	RPM	2598	1732	1299	866	649	520	433
			(68-102)	Fr	0.0008	0.0013	0.0017	0.0025	0.0034	0.0042	0.0051
				Feed (ipm)	2.2	2.2	2.2	2.2	2.2	2.2	2.2

Bhn (Brinell) HRc (Rockwell C) HRb (Rockwell B)

rpm = Vc x 3.82 / DC

ipm = Fr x RPM

reduce speed and feed for materials harder than listed

refer to the SGS Tool Wizard® for complete technical information (www.kyocera-sgstool.com)

Series 142P Metric	Hardness	Vc (m/min)	DC • mm							
			3	6	8	10	12	14	16	
P	CARBON STEELS 1018, 1040, 1080, 1090, 10L50, 1140, 1212, 12L15, 1525, 1536	130	RPM	13733	6867	5150	4120	3433	2943	2575
		≤ 175 Bhn or ≤ 7 HRc (104-155)	Fr	0.104	0.207	0.276	0.345	0.414	0.483	0.552
			Feed (mm/min)	1422	1422	1422	1422	1422	1422	1422
		116	RPM	12279	6140	4605	3684	3070	2631	2302
		≤ 275 Bhn or ≤ 28 HRc (93-139)	Fr	0.093	0.186	0.248	0.310	0.372	0.434	0.496
			Feed (mm/min)	1143	1143	1143	1143	1143	1143	1143
		67	RPM	7109	3555	2666	2133	1777	1523	1333
		≤ 425 Bhn or ≤ 45 HRc (54-80)	Fr	0.079	0.157	0.210	0.262	0.314	0.367	0.419
			Feed (mm/min)	559	559	559	559	559	559	559
	ALLOY STEELS 4140, 4150, 4320, 5120, 5150, 8630, 86L20, 50100	101	RPM	10664	5332	3999	3199	2666	2285	1999
		≤ 275 Bhn or ≤ 28 HRc (80-121)	Fr	0.079	0.157	0.210	0.262	0.314	0.367	0.419
			Feed (mm/min)	838	838	838	838	838	838	838
		61	RPM	6463	3231	2424	1939	1616	1385	1212
		≤ 375 Bhn or ≤ 40 HRc (49-73)	Fr	0.067	0.134	0.178	0.223	0.267	0.312	0.356
			Feed (mm/min)	432	432	432	432	432	432	432
		43	RPM	4524	2262	1696	1357	1131	969	848
		≤ 425 Bhn or ≤ 45 HRc (34-51)	Fr	0.048	0.095	0.127	0.159	0.191	0.223	0.255
			Feed (mm/min)	216	216	216	216	216	216	216
	TOOL STEELS A2, D2, H13, L2, M2, P20, S7, T15, W2	44	RPM	4686	2343	1757	1406	1171	1004	879
		≤ 200 Bhn or ≤ 13 HRc (35-53)	Fr	0.068	0.136	0.181	0.226	0.271	0.316	0.361
			Feed (mm/min)	318	318	318	318	318	318	318
		29	RPM	3070	1535	1151	921	767	658	576
		≤ 375 Bhn or ≤ 40 HRc (23-35)	Fr	0.032	0.065	0.086	0.108	0.129	0.151	0.172
			Feed (mm/min)	99	99	99	99	99	99	99
M	STAINLESS STEELS (FREE MACHINING) 303, 416, 420F, 430F, 440F	93	9856	9856	4928	3696	2957	2464	2112	1848
		≤ 185 Bhn or ≤ 9 HRc (74-112)	0.062	0.062	0.124	0.165	0.206	0.247	0.289	0.330
			610	610	610	610	610	610	610	610
		59	6301	6301	3151	2363	1890	1575	1350	1181
		≤ 275 Bhn or ≤ 28 HRc (48-71)	0.048	0.048	0.097	0.129	0.161	0.193	0.226	0.258
			305	305	305	305	305	305	305	305
	STAINLESS STEELS (DIFFICULT) 304, 316, 321, 13-8 PH, 15-5PH, 17-4 PH, Custom 450	46	4847	4847	2424	1818	1454	1212	1039	909
		≤ 275 Bhn or ≤ 28 HRc (37-55)	0.048	0.048	0.095	0.127	0.159	0.191	0.223	0.254
			231	231	231	231	231	231	231	231
		34	3555	3555	1777	1333	1066	889	762	666
		≤ 375 Bhn or ≤ 40 HRc (27-40)	0.043	0.043	0.086	0.114	0.143	0.171	0.200	0.229
			152	152	152	152	152	152	152	152
K	CAST IRONS Gray, Malleable, Ductile	110	RPM	11633	5816	4362	3490	2908	2493	2181
		≤ 220 Bhn or ≤ 19 HRc (88-132)	Fr	0.109	0.218	0.291	0.364	0.437	0.509	0.582
			Feed (mm/min)	1270	1270	1270	1270	1270	1270	1270
		102	RPM	10825	5413	4059	3248	2706	2320	2030
		≤ 260 Bhn or ≤ 26 HRc (82-123)	Fr	0.109	0.218	0.291	0.364	0.436	0.509	0.582
			Feed (mm/min)	1181	1181	1181	1181	1181	1181	1181

continued on next page

Series 142P Metric	Hardness	Vc (m/min)	DC • mm								
			3	6	8	10	12	14	16		
N	ALUMINUM ALLOYS 2017, 2024, 356, 6061, 7075	≤ 80 Bhn or ≤ 47 HRb	235 (188-282)	RPM	24882	12441	9331	7465	6220	5332	4665
				Fr	0.117	0.235	0.313	0.391	0.470	0.548	0.626
				Feed (mm/min)	2921	2921	2921	2921	2921	2921	2921
		≤ 150 Bhn or ≤ 88 HRb	201 (161-241)	RPM	21327	10664	7998	6398	5332	4570	3999
				Fr	0.119	0.238	0.318	0.397	0.476	0.556	0.635
				Feed (mm/min)	2540	2540	2540	2540	2540	2540	2540
	Copper Alloys Alum Bronze, C110, Muntz Brass	≤ 140 Bhn or ≤ 3 HRc	168 (134-201)	RPM	17773	8886	6665	5332	4443	3808	3332
				Fr	0.048	0.096	0.128	0.160	0.192	0.223	0.255
				Feed (mm/min)	851	851	851	851	851	851	851
		≤ 200 Bhn or ≤ 23 HRc	134 (107-161)	RPM	14218	7109	5332	4265	3555	3047	2666
				Fr	0.048	0.096	0.129	0.161	0.193	0.225	0.257
				Feed (mm/min)	686	686	686	686	686	686	686
S	HIGH TEMP ALLOYS (Nickel , Cobalt, Iron Base) Inconel 601, 617, 625, Incoloy, Monel 400, Rene, Waspaloy	≤ 300 Bhn or ≤ 32 HRc	29 (23-35)	RPM	3070	1535	1151	921	767	658	576
				Fr	0.019	0.038	0.051	0.063	0.076	0.089	0.101
				Feed (mm/min)	58	58	58	58	58	58	58
		≤ 400 Bhn or ≤ 43 HRc	15 (12-18)	RPM	1616	808	606	485	404	346	303
				Fr	0.016	0.031	0.042	0.052	0.063	0.073	0.084
				Feed (mm/min)	25	25	25	25	25	25	25
	TITANIUM ALLOYS Pure Titanium, Ti6Al4V, Ti6Al2Sn4Zr2Mo, Ti4Al4Mo2Sn0.5Si, Ti-6Al4V	≤ 275 Bhn or ≤ 28 HRc	66 (52-79)	RPM	6947	3474	2605	2084	1737	1489	1303
				Fr	0.042	0.084	0.112	0.140	0.168	0.196	0.224
				Feed (mm/min)	292	292	292	292	292	292	292
		≤ 350 Bhn or ≤ 38 HRc	49 (39-59)	RPM	5170	2585	1939	1551	1293	1108	969
				Fr	0.038	0.077	0.102	0.128	0.153	0.179	0.204
				Feed (mm/min)	198	198	198	198	198	198	198
H	TOOL STEELS A2, D2, H13, L2, M2, P20, S7, T15, W2	≤ 440 Bhn or ≤ 47 HRc	26 (21-31)	RPM	2747	1373	1030	824	687	589	515
				Fr	0.029	0.057	0.076	0.096	0.115	0.134	0.153
				Feed (mm/min)	79	79	79	79	79	79	79
		≤ 475 Bhn or ≤ 50 HRc	26 (21-31)	RPM	2747	1373	1030	824	687	589	515
				Fr	0.020	0.041	0.054	0.068	0.081	0.095	0.109
				Feed (mm/min)	56	56	56	56	56	56	56

(Brinell) HRc (Rockwell C) HRb (Rockwell B)
 rpm = (Vc x 1000) / (DC x 3.14)
 mm/min = Fr x RPM
 reduce speed and feed for materials harder than listed
 refer to the SGS Tool Wizard® for complete technical information (www.kyocera-sgstool.com)