



31316 31308



31940



31941



31303



31301

3/8" DRIVE DEEP SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
31308	1/4	2 1/2	11/16	7/16	11/32	1 11/16	7/32	1 1/16					
31310	5/16	2 1/2	11/16	19/32	3/8	1 11/16	5/16	1 1/16					
31312	3/8	2 1/2	11/16	9/16	3/8	1 11/16	3/8	1 1/16					
31314	7/16	2 1/2	11/16	5/8	11/32	1 11/16	7/16	1 1/16					
31316	1/2	2 1/2	3/4	3/4	13/32	1 11/32	15/32	-					
31318	9/16	2 1/2	25/32	25/32	17/32	1 9/16	17/32	-					
31320	5/8	2 1/2	7/8	7/8	19/32	1 9/16	19/32	-					
31322	11/16	2 1/2	15/16	15/16	1/2	1 11/16	21/32	-					
31324	3/4	2 1/2	1	1	9/16	1 11/16	23/32	-					
31326	13/16	2 1/2	1 1/8	1 1/8	9/16	2 1/32	25/32	-					
31328	7/8	2 1/2	1 3/16	1 3/16	21/32	2 1/32	27/32	-					
31330	15/16	2 1/2	1 1/4	1 1/4	21/32	2 1/32	27/32	-					
31332	1	2 1/2	1 5/16	1 5/16	11/16	2	31/32	-					

Fed. Spec: ANSI B107.110

31940 9 Piece 3/8" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31308	1/4	31314	7/16	31320	5/8
31310	5/16	31316	1/2	31322	11/16
31312	3/8	31318	9/16	31324	3/4

31941 13 Piece 3/8" Drive Deep 6 Point Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31308	1/4	31318	9/16	31328	7/8
31310	5/16	31320	5/8	31330	15/16
31312	3/8	31322	11/16	31332	1
31314	7/16	31324	3/4		
31316	1/2	31326	13/16		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for quick engagement on 6 point fasteners.



3/8" DRIVE SPARK PLUG SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
31301	5/8	2 27/32	11/16	27/32	15/32	1 1/16	15/32	1 1/2	11/16	7/8	NA		
31303	13/16	2 29/32	13/16	1 1/16	15/32	1 1/16	15/32	1 1/2	11/16	7/8	NA		

Fed. Spec: ANSI B107.110

Features

- Rubber insert holds spark plug and prevents damage to insulator.

3/8" DRIVE

SOCKETS AND
DRIVE TOOLS