




5T-IW - 100T-I-SETW Single Setting Torque Wrenches



PRODUCT DETAILS

- Factory Pre-Set models are set at the factory to the customer's specified torque setting, and are furnished with a Certificate of Calibration
- Please specify desired torque setting when order is placed
- Featuring a durable, non-slip cushion grip
- Uses universal round shank interchangeable heads
- Audible click and feel impulse torque control mechanism
- Tamper proof torque setting for production line use
- Accuracy: $\pm 3\%$ CW of indicated value, in direction of torque indicator, from 20% to 100% of full scale
- Designed for use on production lines and other applications where a specific torque is required for repetitive operations
- Tamper proof torque setting for production line use Meets or exceeds ASME B107.300-2010



PRODUCT ATTRIBUTES

Product				A	B	C	D	
5T-IW	10-50 lb·in	1.1-5.6 Nm	0.425 in	6.5 in	0.63 in	0.61 in	1 in	0.35 lb
5T-I-SETW	10-50 lb·in	1.1-5.6 Nm	0.425 in	6.5 in	0.63 in	0.61 in	1 in	0.35 lb
10T-IW	50-250 lb·in	5.6-28 Nm	0.425 in	10 in	0.63 in	0.61 in	1 in	0.55 lb
10T-I-SETW	50-250 lb·in	5.6-28 Nm	0.425 in	10 in	0.63 in	0.61 in	1 in	0.55 lb
10ST-IW	60-300 lb·in	6.8-34 Nm	0.425 in	6.2 in	0.68 in	0.86 in	1.4 in	0.75 lb
10ST-I-SETW	60-300 lb·in	6.8-34 Nm	0.425 in	6.2 in	0.68 in	0.86 in	1.4 in	0.75 lb
50T-IW	15-75 lb·in	20-102 Nm	0.425 in	11 in	0.68 in	0.96 in	1.4 in	1.4 lb
50T-I-SETW	15-75 lb·in	20-102 Nm	0.425 in	11 in	0.68 in	0.96 in	1.4 in	1.4 lb
100T-IW	30-150 lb·in	41-203 Nm	0.560 in	19.5 in	0.94 in	0.96 in	1.4 in	2.3 lb
100T-I-SETW	30-150 lb·in	41-203 Nm	0.560 in	19.5 in	0.94 in	0.96 in	1.4 in	2.3 lb
200T-IW	40-200 lb·in	54-271 Nm	0.560 in	23.5 in	0.94 in	0.86 in	1.4 in	2.6 lb
200T-I-SETW	40-200 lb·in	54-271 Nm	0.560 in	23.5 in	0.94 in	0.86 in	1.4 in	2.6 lb
300T-IW	100-300 lb·in	135-406 Nm	0.735 in	27.7 in	1.12 in	1 in	1.4 in	3.9 lb
300T-I-SETW	100-300 lb·in	135-406 Nm	0.735 in	27.7 in	1.12 in	1 in	1.4 in	3.9 lb
600T-IW	120-600 lb·in	162-814 Nm	0.990 in	55 in	1.5 in	1.25 in	1.25 in	10.45 lb
600T-I-SETW	120-600 lb·in	162-814 Nm	0.990 in	55 in	1.5 in	1.25 in	1.25 in	10.45 lb