

ZECA



INDUSTRIAL HOSE REELS

ZECA 9003 SERIES INDUSTRIAL CABLE REEL

With 23' Of PVC Cable



FREE SHIPPING
WHEN YOU ORDER ONLINE*

- AWG 18.
- 3G cable.
- 5A collector.
- Compact size.
- Structural components in shockproof plastic.
- Cable stop engages every 20" using a rack system, easily removed if continuous cable tension is required.
- Zeca-patented custom collector.
- Collector insulation voltage: 2.5kV
- Operating temperature: 23°F to 122°F
- Supplied without power supply lead or plug/socket.

AWG	CABLE LENGTH	MFR #	A&M #	SALE PRICE
18	23'	9003 ZNA	6916737	\$229.00

ZECA AM86 SERIES HOSE REEL

1/2" NPT



FREE SHIPPING
WHEN YOU ORDER ONLINE*

- Hose Reel with 50' of 1/2" KPU hose for compressed air, nitrogen and water applications.
- Exclusive KPU hose, with high resistance to mechanical stress as well as chemical attack from acids and alkalis. At the same time, flexible and easy to handle.
- Suitable for heavy duty environments like workshops, agriculture and different industries.
- Structural components in shockproof plastic.
- Metal swiveling bracket.
- Hose stop engages every 20" using a rack system, easily removed if required.
- Outlet: 1/2" NPT M
- Operating temperature: 5°F to 122°F
- Maximum pressure: 300 PSI

NPT	HOSE LENGTH	MFR #	A&M #	SALE PRICE
1/2"	50'	AM86/13 ZNA	6916742	\$543.00

ZECA 8406 SERIES HOSE REEL

3/8" NPT



FREE SHIPPING
WHEN YOU ORDER ONLINE*

- Hose Reel with 60' of 3/8" black rubber hose for compressed air and water applications.
- ABS Drum.
- Epoxy powder-coated steel bracket.
- Stainless steel screws and bolts.
- Brass outlet fitting.
- Standard joint.
- Adjustable hose stopper.
- Outlet: 3/8" NPT M
- Operating temperature: 5°F to 122°F
- Maximum pressure: 300 PSI

NPT	HOSE LENGTH	MFR #	A&M #	SALE PRICE
3/8"	60'	8406 ZNA	6916743	\$639.00

ZECA AM80 & AM85 SERIES HOSE REELS

With 4AU Hose • 1/4" & 3/8" NPT

- Includes 4AU hose for dimensional stability and high resistance to deformation during compressed air applications.
- Suitable for heavy duty environments and resistant to abrasive applications.
- Structural components in shockproof plastic.
- Metal swiveling bracket.
- Hose stop engages every 20" using a rack system, easily removed if required.
- Operating temperature: 23°F to 104°F
- Maximum pressure: 220 PSI

NPT	HOSE LENGTH	MFR #	A&M #	SALE PRICE
1/4"	32'	AM80/8 4AU ZNA	6916739	\$267.00
1/4"	50'	AM85/8 4AU ZNA	6916740	\$363.00
3/8"	50'	AM85/10 4AU ZNA	6916741	\$374.00

Mfr #AM80/8 4AU ZNA

- Complete with 32' of 5/16" 4AU hose.
- Outlet: 1/8" NPT

Mfr #AM85/8 4AU ZNA

- Complete with 50' of 5/16" 4AU hose.
- Outlet: 1/8" NPT

Mfr #AM8510 4AU ZNA

- Complete with 50' of 5/16" 4AU hose.
- Outlet: 3/8" NPT



MFR #AM80/8 4AU ZNA

MFR #AM85/8 4AU ZNA

FREE SHIPPING
WHEN YOU ORDER ONLINE*

800.864.2660 | WWW.AM-IND.COM

